

SELF-IGNITING LIGHT KM79S

The KM79S is a self-igniting light and The KM79 is a self-igniting light are formed to same shape with take over high reliability in the field of life saving.



■ Features

- ▷ LED light
- ▷ Improve visibility by LED blinking
- ▷ High intensity light emission
- ▷ Continues light emission for a long time
- ▷ Compact size and light weight
- ▷ Corresponds installation height 60m
- ▷ Mercury-free products

■ Approvals and Conformity

SOLAS (1996)

MSC.81(70),LSA code 2.1.2

Rule of ship lifesaving appliance

article 31

M.L.I.T. Japan Type Approval No.5632

■ Specifications

1. Materials: Polycarbonate (Body and Hood)
2. Dimensions: approx.102mm phi, length approx.195mm
3. Weight: approx. 235g (includes battery)
4. Power Supply: Lithium battery
- NOTE: NOT EXCHANGEABLE, NOT RECHARGEABLE**
5. Term of validity: 5 years
6. Light: LED light
7. Light output and Duration: 2 Cd minimum for 2 hours
8. Height of drop test: 60m

■ Request for handling of the bracket

The bracket is designed based on the warranty of 5 years like the self-igniting light itself.

Always replace the bracket together when replacing the self-igniting light.

APPROVED MANUFACTURER BY M. L. I. T. JAPAN

KOA KAKO CO.,LTD.

〒103-0004 2-3-9, Higashi-Nihonbashi, Chuo-ku, Japan

TEL : 03-5835-2924

FAX : 03-5835-1041

<http://www.koa-kako.co.jp>

e-mail: sales@koa-kako.co.jp